

Product	Sinopec Xpert 20W-50 4T Motorcycle Oil SL/MA2
Summary	Product description Sinopec Xpert 20W-50 4T Motorcycle Oil (SL/MA2) is formulated with premium base oils and a multifunctional additive system. It meets the requirements of the Japanese Automobile Standards Organization (JASO) as a JASO MA2 quality product and is successfully registered into the JASO Engine Oil Standards Implementation Panel. At the same time, this product is rated as an API SL service category lubricant.

Available sizes



1L

Applications

Sinopec Xpert 20W-50 4T Motorcycle Oil (SL/MA2) is suitable for use in:

- High performance, air or water cooled, four-stroke gasoline motorcycle engines, where a highest oil quality specification of JASO MA2 is required.
- Also suitable for gasoline motorcycle engines that requires a lower specification.

Features and benefits

- Protects engine and transmission from start to full power.
- Premium engine protection.
- High temperature stability.
- Improves engine power.
- Maintains engine cleanliness.
- Low oil consumption.
- Optimum frictional characteristics to prevent clutch slippage.

Typical data

Sinopec Xpert 20W-50 4T Motorcycle Oil SL/MA2	
SAE grade	20W-50
Kinematic viscosity, cSt @ 100°C, ASTM D 445	19.0
CCS, cP @ -15°C, ASTM D5293	6790
MRV, cP @ -20°C, ASTM D4684	18300
High-temperature, high-shear viscosity (HTHS), cP @ 150°C, ASTM D4683	4.9
Total base number, mg KOH/g, ASTM D 2896	5.8
Pour point, °C, ASTM D 97	-21
Flash point (COC), °C, ASTM D 92	250

These data are given as an indication of typical values, not as exact specifications.

Industry and OEM specifications

Sinopec Xpert 20W-50 4T Motorcycle Oil SL/MA2 meets the performance requirements of the following industry specifications:	
API Service Classification	Petrol/Gasoline: SL
ISO	24254
JASO	T 903 MA2

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2022

© Sinopec 2022

Sinopec Xpert 20W-50 4T Motorcycle Oil SL/MA2