

<b>Product</b>	<b>Sinopec Xtra 5W-40 4T Motorcycle Oil SN/MB</b>
<b>Summary</b>	<b>Product description</b> Sinopec Xtra 5W-40 4T Motorcycle Oil (SN/MB) is formulated with fully synthetic base oils and a multifunctional additive system. It meets the requirements of the Japanese Automobile Standards Organization (JASO) as a JASO MB quality product and is successfully registered into the JASO Engine Oil Standards Implementation Panel. At the same time, this product is rated as an API SN service category lubricant.

Available sizes



0.8 L

## Applications

Sinopec Xtra 5W-40 4T Motorcycle Oil (SN/MB) is suitable for use in:

- Designed for modern scooter engine with dry clutch.
- Fortified with DUAL PROTECH™ technology for enhanced cleanliness and power output.
- Friction modified to JASO MB specification that provide enhanced fuel economy.

## Features and benefits

- Excellent engine start-up and warm up sequence.
- Very good temperature stability with prolonged lubricant life.
- Protects engine from start to full power.
- Ultimate engine protection of its class.
- Excellent cleaning properties.
- Formulated for extremely low oil consumption.
- Provides seal compatibility and protection.
- Friction modified to improve engine power and fuel efficiency.

## Typical data

<b>Sinopec Xtra 5W-40 4T Motorcycle Oil SN/MB</b>	
SAE grade	5W-40
Kinematic viscosity, cSt @ 100°C, ASTM D 445	13.7
CCS, cP @ -30°C, ASTM D5293	6180
MRV, cP @ -35°C, ASTM D4684	29900
High-temperature, high-shear viscosity (HTHS), cP @ 150°C, ASTM D4683	3.8
Total base number, mg KOH/g, ASTM D 2896	7.74
Pour point, °C, ASTM D 97	-36
Flash point (COC), °C, ASTM D 92	242

These data are given as an indication of typical values, not as exact specifications.

## Industry and OEM specifications

<b>Sinopec Xtra 5W-40 4T Motorcycle Oil SN/MB meets the performance requirements of the following industry specifications:</b>	
API Service Classification	Petrol/Gasoline: SN
ISO	24254
JASO	T 903 MB

## Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

## Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2022

© Sinopec 2022

Sinopec Xtra 5W-40 4T Motorcycle Oil SN/MB