

	Product	Sinopec Xtra 10W-40 4T Motorcycle Oil SN/MB
	Summary	Product description Sinopec Xtra 10W-40 4T Motorcycle Oil (SN/MB) is formulated with synthetic technology base oils and a multifunctional additive system. It meets the requirements of the Japanese Automobile Standards Organization (JASO) as a JASO MB quality product and is successfully registered into the JASO Engine Oil Standards Implementation Panel. At the same time, this product is rated as an API SN service category lubricant.

Available sizes



Applications

Sinopec Xtra 10W-40 4T Motorcycle Oil (SN/MB) is suitable for use in:

- Designed for modern scooter engine with dry clutch.
- Fortified with DUAL PROTECH™ technology for enhanced cleanliness and power output.
- Friction modified to JASO MB specification that provides enhanced fuel economy.

Features and benefits

- Perfect balance between premium engine protection and engine start-up/ warm up sequence.
- Protects engine from start to full power.
- Developed for extended engine durability.
- Enhanced temperature stability and outstanding oil loss characteristics.
- Reinforced engine cleanliness and returns original engine power.
- Enhanced seal protection.
- Friction modified to provide better fuel economy.



Typical data

Sinopec Xtra 10W-40 4T Motorcycle Oil SN/MB			
SAE grade	10W-40		
Kinematic viscosity, cSt @ 100°C, ASTM D 445	14.1		
CCS, cP @ -25°C, ASTM D5293	6060		
MRV, cP @ -30℃, ASTM D4684	24300		
High-temperature, high-shear viscosity (HTHS), cP @ 150 °C, ASTM D4683	3.8		
Total base number, mg KOH/g, ASTM D 2896	7.47		
Pour point, °C, ASTM D 97	-33		
Flash point (COC), °C, ASTM D 92	234		

These data are given as an indication of typical values, not as exact specifications.

Industry and OEM specifications

Sinopec Xtra 10W-40 4T Motorcycle Oil SN/MB meets the performance requirements of the following industry specifications:

API Service Classification	Petrol/Gasoline: SN
ISO	24254
JASO	T 903 MB

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2022

© Sinopec 2022

Sinopec Xtra 10W-40 4T Motorcycle Oil SN/MB



The information contained herein is subject to change without notification due to continuing research & development therefore properties may be subject to slight variations.