

Product	Sinopec Xtra 15W-40 4T Motorcycle Oil SL/MB
Summary	Product description Sinopec Xtra 15W-40 4T Motorcycle Oil (SL/MB) is formulated with premium base oils and a multifunctional additive system. It meets the requirements of the Japanese Automobile Standards Organization (JASO) as a JASO MB quality product and is successfully registered into the JASO Engine Oil Standards Implementation panel. At the same time, this product is rated as an API SL service category lubricant.

Available sizes



0.8 L

Applications

Sinopec Xtra 15W-40 4T Motorcycle Oil (SL/MB) is suitable for use in:

- Designed for modern scooter engine with dry clutch.
- Friction modified to JASO MB specification that provide enhanced fuel economy.

Features and benefits

- Protects engine from start to full power.
- Reduces noise and vibration.
- High temperature stability and low oil consumption.
- Maintains engine cleanliness and returns original engine power.
- Friction modified to provide better fuel economy.

Typical data

Sinopec Xtra 15W-40 4T Motorcycle Oil SL/MB	
SAE grade	15W-40
Kinematic viscosity, cSt @ 100°C, ASTM D 445	14.6
CCS, cP @ -20°C, ASTM D5293	5480
MRV, cP @ -25°C, ASTM D4684	20700
High-temperature, high-shear viscosity (HTHS), cP @ 150°C, ASTM D4683	3.9
Total base number, mg KOH/g, ASTM D 2896	7.39
Pour point, °C, ASTM D 97	-27
Flash point (COC), °C, ASTM D 92	236

These data are given as an indication of typical values, not as exact specifications.

Industry and OEM specifications

Sinopec Xtra 15W-40 4T Motorcycle Oil SL/MB meets the performance requirements of the following industry specifications:	
API Service Classification	Petrol/Gasoline: SL
ISO	24254
JASO	T 903 MB

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. Please consult the SDS for more detailed advice on handling; SDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected.

Issued: March 2022

© Sinopec 2022

Sinopec Xtra 15W-40 4T Motorcycle Oil SL/MB